

MODULAR CONTACTORS - DIN RAIL MOUNT



FEATURES & BENEFITS

- Compact and modular
- Quiet operation
- For control of power circuits including:
 - » lighting
 - » motors
 - » fans
 - » heating
 - » ventilation
 - » pumps
 - » home automation
- Ideal for remote switching
- Comprehensive range.

SPECIFICATIONS

Control voltage:

- 240Vac

Operating frequency:

- 50/60Hz

Auxiliary contactor:

- CON-AUX/1NO1NC

Auxiliary contact (breaking capacity):

- AC12 5A 240Vac
- AC15 2A 230Vac
- DC13 1A 130Vac

Operating temperature:

- -5°C to +50°C

Storage temperature:

- -40°C to +70°C

Voltage rating:

- 2P - 250 V AC
- 4P - 400 V AC

Endurance (O/C)

- 100,000 cycles

Max no. of switching a day:

- 100

Insulation voltage (Ui)

- 500 Vac

Pollution degree

- 2

Rated impulse withstand voltage

- 2.5kV (4kV for 12/24/48V AC)

Weatherproof rating:

- Device only: IP20
(Requires enclosure)

Conforms to:

- IEC 60068-1



MODULAR CONTACTOR RANGE

| Code | Description | Packing | MOQ | Ctn |
|----------------|---------------------------------------|---------|-----|-----|
| CON-25A/1NO1NC | Modular Contactor 240Vac 25A 1NO+1NC | 1 | 1 | 120 |
| CON-25A/2NO | Modular Contactor 240Vac 25A 2NO | 1 | 1 | 120 |
| CON-25A/2NO2NC | Modular Contactor 240Vac 25A 2NO+2NC | 1 | 1 | 50 |
| CON-25A/4NO | Modular Contactor 240Vac 25A 4NO | 1 | 1 | 50 |
| CON-40A/2NO2NC | Modular Contactor 240Vac 40A 2NO+2NC | 1 | 1 | 40 |
| CON-40A/4NO | Modular Contactor 240Vac 40A 4NO | 1 | 1 | 40 |
| CON-63A/2NO2NC | Modular Contactor 240Vac 63A 2NO+2NC | 1 | 1 | 40 |
| CON-63A/4NO | Modular Contactor 240Vac 63A 4NO | 1 | 1 | 40 |
| CON-AUX/1NO1NC | Auxiliary Contactor 240Vac 6A 1NO+1NC | 1 | 1 | 120 |